



FNR1210series



CONSTRUCTION



FEATURES

Magnetically structure
Low DC resistance
Large Current Capability



APPLICATIONS

Hard Disk Drives
Car audio equipment
Tablet PC
Navigation system
SSD
Touch Panel

SPECIFICATIONS

Operating temperature range	-40 to +125°C
Storage temperature range	Under 25°C
Packaging style	Taping
Quantities	3,000 pieces/reel


SHAPE AND DIMENSIONS



(Unit: mm)

TYPE	A	B	C	D	E	F	G
FNR1210	1.2±0.2	1.2±0.2	1.0max	0.5±0.1	1.3	0.5	0.4

PRODUCT IDENTIFICATION (ex.)



ELECTRICAL CHARACTERISTICS


Part No.	Inductance (uH)	Inductance tolerance	Test Frequency (MHz)	DC Resistance (Ω) $\pm 20\%$	Saturation current Isat(mA)		Temperature rise current Irms(mA)	
					Typ.	Max.	Typ.	Max.
FNR1210T-R24N	0.24	$\pm 30\%$	1	0.058	2000	1500	2000	1500
FNR1210T-1R0N	1.0	$\pm 30\%$	1	0.200	1400	1200	1400	1200

*The saturation current value (Isat) is the DC current value having inductance decrease down to 30% (at 25°C)

*The temperature rise current value (Irms)is the DC current value having temperature increase up to 40°C (at 25°C)


*Rated current: smaller value of either Isat or Irms.

RECOMMENDED SOLDERING CONDITIONS




PACKAGE

(1) Taping specifications



Type	W	P	A	B	C	T1	T2
FNR1210	8	3.5	4.0	1.35	1.35	0.23	1.2

(2) Reel Specifications



Unit:mm

Type	A	B	C	D	Q'ty/Reel
FNR1210	180±0.1	60±0.1	14.5±0.1	10±0.15	3000

Label

Wire Wound Power Inductors
 FNR12□□T-□□□M/N
 3,000PCS
 Lot No. _____
 FUMIWA TECHNIAL CO., LTD.

Type	Q'ty
PCS/Reel	3000
Reel/inner Box	15000
Inner Box/Carton	60000